San Joaquin Valley **Unified Air Pollution Control District**

Guideline for Expedited Application Review (GEAR) **Abrasive Blasting Operations**

Approved By: Signed	Date: 5/31/2016
Arnaud Marjollet	
Director of Permit Services	

PURPOSE: To outline the procedures for expedited processing of Authority to Construct (ATC) applications for abrasive blasting operations. These procedures will apply to processing of applications received over the counter or through the mail.

I. **APPLICABILITY**

This policy applies to applications for Authority to Construct new (confined or unconfined) abrasive blasting operations. Abrasive blasting operations do not include the equipment that supplies the compressed air or any bulk storage vessels that may be present. If such equipment requires an Authority to Construct on its own, it must be applied for separately and is not covered by this policy.

II. PERMIT APPLICATION AND SUPPLEMENTARY FORMS

The applicant must complete a regular ATC application form and the Abrasive Blasting Supplemental Application Form (Attachment I).

III. PRIORITY PROCESSING

If requested by the applicant, the applications will be processed on an expedited basis if a complete application form and the application filing fees for each permit unit are submitted. Expedited projects shall be processed within 30 days of receipt of a complete application.

In order to meet the expedited time frame, the engineer assigned for preliminary review will deem the application complete (if appropriate), write the application review, and finalize the project. The application review and final ATC will be submitted to the [lead engineer/supervisor/manager] for review and signature.

The priority processing will be preempted if the application is subject to any public noticing requirements, including school notice per California Health & Safety Code (CH&SC) 42301.6 (within 1,000 feet of any K-12 school).

IV. APPLICATION REVIEW

In order to standardize the application reviews for this source category, the application review found in [AirNet] will be used as a base document. The following pages are a hard copy version of this standard review. This hard copy version for the GEAR Policy Manual includes a copy of the required supplemental application form (Attachment I) and the standard ATC conditions. The actual application review will only have a draft ATC attached to it. This will minimize the number of pages for the expedited review.

The use of this standard Application Review will ensure that the proposed project complies with all applicable prohibitory rules.

V. EQUIPMENT DESCRIPTION

To ensure uniformity, the following standard description will be used in the database:

The ATC will specify if the operation is for confined blasting, unconfined blasting, or both, consistent with the applicant's proposal.

VI. AUTHORITY TO CONSTRUCT CONDITIONS

To ensure uniformity, a standard set of conditions will be used as a base for all applications (see Engineer Evaluation attached).

VII. APPLICABLE REQUIREMENTS

For applicable definitions see § 92000 of the California Code of Regulations (CCR).

A. Statewide Standards

Pursuant to California Health and Safety Code § 41900, the air pollution standards for abrasive blasting operations are set statewide by a committee of 11 members formed in accordance with § 41901.

California Health and Safety Code § 41904 states that "the standards shall be statewide, and no rule or regulation of any district that is applicable to sandblasting operations shall be stricter or less strict than the standards adopted by the state board pursuant to the recommendations of the committee."

B. Permit Requirements

§ 92100 of the California Code of Regulations states that the "standards in this subchapter are not intended to prohibit air pollution districts from enforcing their permit regulations as they apply to abrasive blasting equipment."

Therefore, permits are required in accordance with District Rule 2010 and subject to exemptions in District Rule 2020. Per District Policy ADM 1230, uncontrolled emissions from an abrasive blasting operation designed to include a blasting cabinet with an integral filtration system shall be determined to be those emissions which occur after emissions are reduced by the filtration system. This should be considered in determining if the unit is and subject to exemptions in District Rule 2020.

Emissions calculations are required for permit requirement determination: see calculation section of Engineer Evaluation attached.

If abrasive blasting operation is permit exempt, use permit exemption letter from AIRnet, Form/Letter.

C. New Source Review Rule Applicability

§ 41905 of the California Health and Safety Code states that "the (state) standards, however, shall not supersede any rule or regulation of any district governing permanent sandblasting operation or equipment, which rule or regulation was in effect on January 1, 1974."

All new source review rules in the eight counties in the District were adopted after January 1, 1974. Therefore, the NSR requirements shall not apply to abrasive blasting operations conducted within the District.

In determining the NSR requirements, the emissions from abrasive blasting operations shall be excluded from the stationary source emissions.

D. Nuisance Rule Applicability

Section 4.0 of District Rule 4102 prohibits of air contaminants, which could cause injury, detriment, nuisance or annoyance to the public.

The District's Risk Management Policy for Permitting New and Modified Sources (APR 1905, 3/2/01) requires that a Risk Management Review is performed for any increase in hourly or annual emissions of Hazardous Air Pollutants (HAPs). HAPs are limited to substances included on the list in CH&SC 44321 and that have an OEHHA approved health risk value.

E. Internal Combustion Engine Rule Applicability (if an internal combustion engine provides the compressed air for the abrasive blasting operation)

For purposes of § 41905 of the California Health and Safety Code, "sandblasting operation or equipment" does not include the equipment used to provide the compressed air. Therefore, any engine used to provide air or electricity for the blasting operation will not be exempt from Rules 2201, 4701, or any other prohibitory rules. Such engines shall be evaluated separately from the abrasive blasting operation.

F. Specific Requirements – 17 CCR, Subchapter 6

For determining the applicable requirements under § 92000 through § 92540 CCR, self-contained abrasive blasting operations such as blasting cabinets that vent to control devices are considered to be operations conducted "within a permanent building". If, however, a blasting cabinet is being operated without a control device and is not located within a building, it would be considered an operation conducted "outside a permanent building", and would be specified on the ATC as an unconfined operation.

1. Visible Emissions (§ 92200 CCR)

- a) Visible emissions from the abrasive blasting operation shall be less than 40% opacity when conducted outside a permanent building.
- b) Visible emissions from the abrasive blasting operation shall be less than 20% opacity when conducted within a permanent building.

2. Nuisance Prohibition (§ 92210 CCR)

Compliance with the statewide regulations does not exempt any person from complying with Section 41700 of the Health and Safety Code, nor from complying with any state statutory common law nuisance prohibition.

3. Performance Standards (§ 92500 CCR)

- a) All abrasive blasting operations must be conducted within a permanent building except for when one or more of the following conditions apply:
 - (i) Steel or iron shot/grit is used exclusively.
 - (ii) The item to be blasted exceeds 8 feet in any dimension.
 - (iii) The surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted.
- b) Abrasive blasting operations not conducted within a permanent building must use one or more of the following exclusively:
 - (i) Wet abrasive blasting.
 - (ii) Hydroblasting.
 - (iii) Vacuum blasting.
 - (iv) Abrasives certified by CARB for permissible dry outdoor blasting.
- c) Abrasive blasting of stucco and concrete shall be performed by wet blasting, hydroblasting, or vacuum blasting with the following exceptions (§ 92520 CCR):

Dry blasting with a certified abrasive may be used for:

- (i) Window and door returns and frames.
- (ii) Eaves, overhangs, and ceilings.
- (iii) Sweep abrasive blasting except for stucco surfaces.
- (iv) Completely shrouded structures or blast areas that effectively control emissions.
- (v) Abrasive cleaning operations, other than aggregate exposure or paint removal related to new concrete construction or repair activity, if such operations are performed onsite.

VIII. UPDATES

This GEAR will be updated as necessary to accommodate any changes in prohibitory rules or other items affecting the policy.

The attached bibliography lists items which are referenced in this GEAR. Changes to the listed items may necessitate revisions to this document. Additionally, alterations to this policy may trigger changes to some of the listed items.

The Permitting Handbook will also be updated whenever this GEAR document is updated.

Each update will be submitted to the GEAR coordinator for review and the coordinator will forward the updates for the Director's approval.

Confined Abrasive Blasting Operation (Cabinet Located Inside a Building/Room)

- {271} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule]
- {52} The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
- {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
- {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
- {1992} Abrasive blasting operations conducted within the blasting cabinet shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]

Confined Abrasive Blasting Operation (Cabinet Located Outside a Building/Room)

- {271} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule]
- {52} The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
- {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
- {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
- {1992} Abrasive blasting operations conducted within the blasting cabinet shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]

Confined Abrasive Blasting Operation (Located Inside a Building/Room Without Cabinet)

- {271} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule]
- {52} The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
- {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
- {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
- {1474} Abrasive blasting operations conducted within a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]

Unconfined Abrasive Blasting Operation (Located Outside a Building Without Cabinet)

- {271} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule]
- {52} The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
- {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
- {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
- {1482} Unconfined abrasive blasting operations shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
- {1990} Except as otherwise provided in this permit, abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used. [92500 CCR]
- {1991} Abrasive blasting of items exceeding 8 feet in any dimension, or of a surface situated at its permanent location, or no further away from its permanent location than is necessary to allow the surface to be blasted, may be performed outside a permanent building only if one of the following is used: steel or iron shot/grit; abrasives certified by CARB for permissible dry outdoor blasting; wet abrasive blasting, hydroblasting; or vacuum blasting. [92500 CCR]

Confined (Located Inside a Building, Without a Cabinet) AND Unconfined (Located Outside a Building, Without a Cabinet) Abrasive Blasting Operation

- {271} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule]
- (52) The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
- {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
- {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
- {1474} Abrasive blasting operations conducted within a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
- {1482} Unconfined abrasive blasting operations shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
- {1990} Except as otherwise provided in this permit, abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used. [92500 CCR]
- {1991} Abrasive blasting of items exceeding 8 feet in any dimension, or of a surface situated at its permanent location, or no further away from its permanent location than is necessary to allow the surface to be blasted, may be performed outside a permanent building only if one of the following is used: steel or iron shot/grit; abrasives certified by CARB for permissible dry outdoor blasting; wet abrasive blasting, hydroblasting; or vacuum blasting. [92500 CCR]

ATTACHMENT ISupplemental Form

San Joaquin Valley Unified Air Pollution Control District Supplemental Application Form

Abrasive Blasting

This form must be accompanied by a completed Application for Authority to Construct and Permit to Operate form

PERMIT TO BE ISSUED	TO:		
LOCATION WHEDE TH	HE EQUIPMENT WILL BE OPERATED:		
LUCATION WIERE III	E EQUIPMENT WILL DE OPERATED:		
	PROCESS DESCRIPTION		
	Manufacturer:		
	Material Name:		
Abrasive Used	Material Type: [] Sand [] Grit [] Shot [] Other :		
	Flow Rate: lb/hr		
	Amount of Material used:lb/daylb/yr		
Plasting Type	[] Confined [] Unconfined		
Blasting Type	If unconfined: [] Wet [] Dry [] Vacuum [] Hydroblasting		
Diagted Item	Description:		
Blasted Item	Dimensions (ft) Length: Width: Height:		
	EQUIPMENT DESCRIPTION		
Manufacturer:			
Blasting Unit	Model:		
	Capacity (lb):		
Nozzles	Number of Nozzles: Maximum Inner Diameter : in		
	Manufacturer:		
	Model:		
Compressor	[] Electric [] Gasoline [] Diesel [] Natural Gas Rating:hp Note: If engine is rated at greater than 50 hp an IC Engine Supplemental Application form is required.		
	Air Flow Rate (cfm): @ psi		

EMISSIONS CONTROL EQUIPMENT

(if applicable) Booth Filtration Method: [] Dry Filter [] Water-Wash [] Oil-Wash Number of Filters: in L in W in H					in H	
						in H
	Exhaust Fan Specifications	s: Diameter	in M	otor Ratinghp		
	III	EALTH DICK	ACCEC			
Operating Hou				per day, and	hours per year	
Operating from	Distance to nearest			is measured from the p		ocation to the
	Residence	feet		oundary of the nearest	•	
D (D (Direction to nearest Residence		Direction	from the stack to the re	eceptor, i.e. No	rtheast or South.
Receptor Data	Distance to nearest	feet	Distance is measured from the proposed stack location to the nearest boundary of the nearest office building, factory, store, etc.			
receptor But		reet			*	ocation to the
receptor Butt	Business Direction to nearest	leet	nearest b	oundary of the nearest	office building,	ocation to the factory, store, etc.
receptor But	Business Direction to nearest Business		nearest b	oundary of the nearest of the reach to the re	office building,	ocation to the factory, store, etc.
Treceptor Butt	Business Direction to nearest		nearest b	oundary of the nearest of the reach to the re	office building,	ocation to the factory, store, etc.
Stack	Business Direction to nearest Business	feet	nearest b Direction	oundary of the nearest of the reach to the re	office building,	ocation to the factory, store, etc.
	Business Direction to nearest Business Release Height	feet	nearest b Direction above the	oundary of the nearest of from the stack to the reground	office building,	ocation to the factory, store, etc.
Stack	Business Direction to nearest Business Release Height Stack Diameter	feet feet inch	nearest b Direction above the nes, at poin pe [] Fi	oundary of the nearest of from the stack to the reground at of release	office building,	ocation to the factory, store, etc.
Stack	Business Direction to nearest Business Release Height Stack Diameter Rain Cap Direction of Flow	feet feet inch	nearest b Direction above the nes, at poin pe [] Fi	oundary of the nearest of from the stack to the reground at of release [] None [] Horizontal	office building,	ocation to the factory, store, etc.
Stack Parameters	Business Direction to nearest Business Release Height Stack Diameter Rain Cap Direction of Flow Flowrate:	feetfeetinch [] Flapper-ty [] Vertically acfm	nearest b Direction t above the nes, at poin type [] Fi Upward Tempera	oundary of the nearest of from the stack to the reground at of release [] None [] Horizontal	office building,	ocation to the factory, store, etc.
Stack Parameters Exhaust Data	Business Direction to nearest Business Release Height Stack Diameter Rain Cap Direction of Flow Flowrate:	feetfeetinch [] Flapper-ty [] Vertically acfmnse population) [nearest b Direction t above the nes, at poin Upward Tempera Rural (oundary of the nearest of from the stack to the reground at of release [Ixed-type [I]] None [I]] Horizontal ture:°F area of sparse population)	office building,	ocation to the factory, store, etc.
Stack Parameters Exhaust Data	Business Direction to nearest Business Release Height Stack Diameter Rain Cap Direction of Flow Flowrate:	feetfeetinch [] Flapper-ty [] Vertically acfm	nearest b Direction t above the nes, at poin Upward Tempera Rural (oundary of the nearest of from the stack to the reground at of release exed-type [] None [] Horizontal ture:°F area of sparse population) SE ONLY	office building,	ocation to the factory, store, etc. rth or Southwest.

BIBLIOGRAPHY

Rules and Regulations			
Rule Number	Title	Last Updated	
District Rule 2201	New and Modified Stationary Source Review Rule	12/19/2002	
District Rule 4102	Nuisance	12/17/1992	
Title 17 CCR	Title 17 California Code of Regulations -	6/1/1991	
	Subchapter 6, § 92000 thru § 92540		
CH&SC 41900	California Health and Safety Code § 41900 thru	1997	
thru 41905	§ 41905		

District Policies			
Policy Number	Title	Last Updated	
ADM 1230	Interpretation of "not specifically listed in Section 5.0", and "uncontrolled emissions" in Rule 2020, Exemptions.	4/18/1995	

Electronic Documents			
Document Name	Title	Last Updated	
	Standard Application Review for Abrasive Blasting Operations	03/11/2002	

Miscellaneous			
Item	Title	Last Updated	
Supplemental	Supplemental Application Form for Abrasive	03/11/2002	
Form	Blasting		
General	General Conditions from PAS Abrasive Section	03/11/2002	
Conditions	Condition Category		